







PAOLO ASTORI s.r.l.
via Mirabella 9-MAGGIATE SUP.
I 28013-GATTICO (NO)



JO310
JO311



DETTAGLIO DEI FORI DI RIVETTATURA SVASATI
detail of bottom c/sunk rivet holes

dimensioni in mm. dimensions in mm.

codice dimensioni dimensions code	filettatura thread T	tolleranza tolerance	A max.	C min.	E ±0,1	F 0 +0,2	H max.	K min.	N ±0,25	R max.	S max.	massa (kg x 1000) mass (kg x 1000)
03	MJ3 x 0,5	4H-6H	11,7		6,0	2,5	3,2		4,8	3,0	1,0	1,0
04	MJ4 x 0,7	4H-6H	15,7	4,4	8,5	2,5	5,8	2,2	4,8	4,0	1,0	1,5
05	MJ5 x 0,8	4H-6H	17,2	5,5	9,5	2,5	6,9	2,4	4,8	4,5	1,0	2,4
06	MJ6 x 1	4H-5H	19,7	6,5	11,0	2,5	8,1	2,7	4,8	5,0	1,2	3,1
08	MJ8 x 1	4H-5H	21,2	8,5	11,0	3,0	9,9	2,7	5,7	6,5	1,5	6,7
10	MJ10 x 1,25	4H-5H	25,8	10,5	13,0	3,5	12,0	3,0	6,6	8,1	1,6	11,7

cod. materiali <i>material code</i>	materiale <i>material</i>	finitura <i>finish</i>	durezza HR _C <i>hardness HR_C</i>	classe resistenza <i>strenght class</i>	classe temperatura <i>temperature class</i>
JO310L	W1.7214.4 acciaio- <i>steel</i> 25CrMo4	cadmiatura+MoS ₂ <i>cadmium plating+MoS₂</i>	43 max.	1100 MPa	235° C
JO310C		cadmiatura <i>cadmium plating</i>			235° C
JO311X	W1.4944.4 lega A286 <i>A286 alloy</i>	passivazione <i>passivation</i>	27 min.		425° C
JO311L		passivazione+MoS ₂ + puntino verde <i>passivation+MoS₂</i> <i>+ green dot</i>			315° C
JO311A		argentatura <i>silver plating</i>			425° C

FILETTO: profilo MJ ISO5855.

MARCATURA: simbolo α del costruttore e caratteri MJ.

NORMA di costruzione e controllo: LN65016.

DESIGNAZIONE ASTORI: codice materiali-codice dimensioni.

Esempio: JO310C-05 indica una olivetta a disegno JO310, in acciaio cadmiato, filettatura MJ5

VARIAZIONI: aggiungere una K al codice dimensioni per le olivette con i fori di rivettatura svasati.

THREAD: according to MJ profile ISO 5855.

MARKING: manufacturer symbol α and MJ letters

PROCUREMENTS specification: LN65016.

ASTORI CALL OUT: materials code-dimensions code.

Example: JO310C-5 designates a plate nut according to JO310 drawing, in steel, cadmium plated, with MJ5 thread.

VARIATIONS: add a K to dimensions code for plate nuts with countersunk rivet holes.

Reference DIN65238 DIN65239	OLIVETTA AUTOFRENANTE AD ANGOLO, FISSA FILETTATURA MJ ANCHOR NUT, SELF-LOCKING CORNER, FIXED, MJ THREAD	JO310 JO311
---	--	------------------------------