

ZONE	LTR	REVISIONS DESCRIPTION	DATE	APPROVED
	A	SEE CHG NOTE 10365	5-10-79	JEE
	B	SEE CHG NOTE 10398	7-5-79	JEE
	C	SEE CHG NOTE 10472	7-21-79	JEE

ITEM NO.	QTY REQD	ISSUE EDIT	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SIZE OR SPECIFICATION
10	1		1046-1	LEVER (B P/N 222-031-451-101)	
9	2		AN 316-6	NUT	
8	2		MS 168-11-4	BOLT	
7	1		1048-401	LINK ASSY	
6	1		1047-1	BELLCRANK (B P/N 222-031-448-101)	
5	1		AN 960C10	WASHER	
4	1		AN 502-10-6	SCREW	
3	1		1000-402	HANDLE ASSY	RH, SHORT SPINDLE
2	2		1048-401	ROD ASSY	
1	2		1044-401	LATCH ASSY	

PARTS LIST

NEXT ASSY | USED ON | NEXT ASSY | FINAL ASSY

APPLICATION | QTY REQD

DO NOT SCALE THIS DRAWING

- INTERPRET DRAWING IN ACCORDANCE WITH MIL-D-1000
- REMOVE ALL BURRS, BREAK SHARP EDGES .010 MAX
- ALL CORNER AND FILLET RADII TO BE .020 MAX

DRAWN BY	JEE	1-15-79
CHECKED	BLE	1-15-79
ENGR APPR		1-15-79
PROJECT		3-1-79

SKYLOCK INDUSTRIES, INC.
SO. EL MONTE, CALIFORNIA

DOOR BOLTING SYSTEM

SIZE E | CAGE CODE NO. 51941 | DRAWING NO. 20309 | REV

SCALE 1/1 | WT | SHEET 1 OF 1

20309 1/1

1. WITH LATCH SUPPORTED ONLY THRU ATTACHMENT HOLES, LATCH ASSY IS CAPABLE OF WITHSTANDING 133 LB LIMIT LOAD APPLIED AS SHOWN WITHOUT PERMANENT DEFORMATION AND A 200 LB ULTIMATE LOAD WITHOUT FAILURE.
2. HANDLE ASSY WILL WITHSTAND THE FOLLOWING TORQUE LOADS:
   - 200 IN LBS WITH NO YIELD
   - 600 IN LBS WITH NO FAILURE
   APPLIED AS SHOWN ; REACTED BY SHAFT
3. ROLLER WILL WITHSTAND A 60 LB LOAD APPLIED NORMAL TO ITS AXIS WITHOUT PERMANENT DEFORMATION.
1. DWG CONFORMS WITH BELL DWG 222-031-405

NOTES: UNLESS OTHERWISE SPECIFIED