







PAOLO ASTORI

PAOLO ASTORI s.r.l.
via Mirabella 9-MAGGIATE SUP.
I 28013-GATTICO (NO)



PO354
PO355



DETTAGLIO DEI FORI DI RIVETTATURA SVASATI
detail of bottom c'sunk rivet holes

dimensioni in mm. dimensions in mm.

codice dimensioni dimensions code	filettatura thread T	tolleranza tolerance	A max.	B max.	C ±0,05	E ±0,1	F 0 +0,2	H max.	K min.	N ±0,25	R max.	S max.	massa (kg x 1000) mass (kg x 1000)
40	1/4 - 28	UNJF - 3B	15,0	11,1	6,45	7,14	2,5	7,2	1,6	5,1	5,2	1,2	2,1

cod. materiali material code	materiale material	finitura finish	durezza HR _C hardness HR _C	classe resistenza strenght class	classe temperatura temperature class
PO354L	W1.7214.4 acciaio-steel	cadmiatura+MoS ₂ cadmium plating+MoS	43 max.	900 MPa	235°C
PO354C		cadmiatura cadmium plating			235°C
PO355X	W1.4944.4 lega A286 A286 alloy	passivazione passivation	27 min.		425°C
PO355L		passivazione+MoS ₂ + punto verde passivation+MoS ₂ + green dot			315°C
PO355A		argentatura silver plating			425°C

FILETTO: in accordo a MIL-S-8879 prime della frenatura.
 MARCATURA: simbolo α del costruttore.
 NORMA di costruzione e controllo: NASM25027.
 DESIGNAZIONE ASTORI: codice materiali-codice dimensioni.
 Esempio: PO354C-40 indica una olivetta a disegno PO354, in acciaio cadmiato, filettatura 1/4-28
 VARIAZIONI: aggiungere una K al codice dimensioni per le olivette con i fori di rivettatura svasati.

THREAD: in accordance to MIL-S-8879 before locking.
 MARKING: manufacturer symbol α
 PROCUREMENTS specification: NASM25027.
 ASTORI CALL OUT: materials code-dimensions code.
 Example: PO354C-40 designates a plate nut according to PO354 drawing, in steel, cadmium plated, with 1/4-28 thread.
 VARIATIONS: add a K to dimensions code for plate nuts with countersunk rivet holes.

Reference	OLIVETTA AUTOFRENANTE, MINIATURA AD ANGOLO, FISSA, filett. In pollici ANCHOR NUT, SELF-LOCKING, MINIATURE CORNER, FIXED. American thread	PO354 PO355
-----------	---	------------------------